

TW-1516TP

Integrated 5-in-1 15" TFT LCD display, Keyboard, Touchpad, 16-port KVM Switch in a 1U 19" width rack-mount drawer.



Key Features

- **AUO 15" A grade XGA TFT LCD 1024 x 768**
- **16 Ports KVM Switch with full database for supporting various servers & keyboard / mouse**
- **Button switch & hot-key available, both for switching channels**
- **Zippy keyboard in 104keys, with touch pad**
- **Auto scan mode for monitoring PCs**
- **Built-in rail self-locking device**

Model Name	TW-1516TP
Weight	13kg(N.W.) / 16kg(G.W.)
Dimensions(WxHxD)	484 x 44 x 650mm
Keyboard and Touchpad	104 Keys windows compliant keyboard, built-in touch pad
Display	
Size	15" TFT LCD
Resolution	XGA 1024 x 768
Brightness	400cd/m2
Contrast Ratio	300:1(Typ.)
Display Colors	16.2M
Pixel Pitch (HxV)	0.297 x 0.297mm
LCD life	40,000hrs
Interface	Analog RGB input
Connectors	VGA, PS/2 keyboard, and male PS/2 mouse
Power Supply	
Input	AC 100 ~ 240, 50 ~ 60Hz,
Output	12V / 3.7A
Operation Environment	
Temperature	0°C to 50°C (32°F to 122°F)
Vibration	10 to 58Hz, ±0.15mm; 58 to 500 Hz, 2G
Agency Approvals	CE/FCC Part15, Class A; EN60950 Safety

TW-1716TP

Integrated 5-in-1 17" TFT LCD display, Keyboard, Touchpad, 16-port KVM Switch in a 1U 19" width rack-mount drawer.



Key Features

- **AUO 17" A grade SXGA TFT LCD 1280 x 1024**
- **16 Ports KVM Switch with full database for supporting various servers & keyboard / mouse**
- **Button switch & hot-key available, both for switching channels**
- **Zippy keyboard in 104keys, with touch pad**
- **Auto scan mode for monitoring PCs**
- **Built-in rail self-locking device**

Model Name	TW-1716TP
Weight	13kg(N.W.) / 16kg(G.W.)
Dimensions(WxHxD)	484 x 44 x 650mm
Keyboard and Touchpad	104 Keys windows compliant keyboard, built-in touch pad
Display	
Size	17" TFT LCD
Resolution	SXGA 1280 x 1024
Brightness	300cd/m ²
Contrast Ratio	300:1(Typ.)
Display Colors	16.2M
Pixel Pitch (HxV)	0.264 x 0.264mm
LCD life	40,000hrs
Interface	Analog RGB input
Connectors	VGA, PS/2 keyboard, and male PS/2 mouse
Power Supply	
Input	AC 100 ~ 240, 50 ~ 60Hz
Output	12V / 3.7A
Operation Environment	
Temperature	0°C to 50°C (32°F to 122°F)
Vibration	10 to 58Hz, ±0.15mm; 58 to 500 Hz, 2G
Agency Approvals	CE/FCC Part15, Class A; EN60950 Safety